

Baumuster 93231712

Typ 4146 K 8X4/4 5100

FIN-Nummer WDB 932317 1 L 268481

Lack/Lackzusatz	
LA1 9147	arctic white

Axle load distribution	
TT8	Weight variant 44.0 t (9.0/9.0/13.0/13.0)

Engine	
MX0	Engine, V6, LA, 335 kW/456 hp, 1800 rpm
MS4	BlueTec 4 (Euro 4)
M49	Tandem air cleaner system
K81	Fuel pre-filter, heated water separator
MZ3	Viscous coupling, electromagnetic, for fan
MZ7	Air compressor, 1-cylinder, regulated
M89	Flame system

Clutch & transmission	
G81	Clutch, reinforced
GC2	Transmission G 240-16/11.7-0.69
N55	Transmission oil cooling
GS3	Gearshift, hydraulic
NH2	PTO, layshaft MB 131-2c

Axles & suspension	
A91	Front axle, straight version
AL5	Front axle 9.0 t
AM3	Rear axle H7, 13.0 t, crown wheel 300
AQ7	Axle ratio $i = 4.833$ (HL7)
QD1	Front spring, 9,0 t
QF3	Rear spring, 15,0 t, hard
CD3	Stabiliser, rear axle
CD4	Stabiliser, reinforced, 2nd rear axle

Wheels & tyres	
A1 W48K26 80 x 2	385/65 R 22,5# TL Highway cross country (S+G) "K"
A2 W48K26 80 x 2	385/65 R 22,5# TL Highway cross country (S+G) "K"
A3 F18K27 80 x 9	315/80 R 22,5# TL Highway cross country (S+G) "K"
RA9	Tapered rims, 11.75x22.5, on front axle
R38	Tapered rims, 9.00x22.5

R60	Spare wheel carrier, provisional
R04	Wheel nut cap
RM8	Tyre make, specially requested, Michelin
R87	Spare wheel/spare wheel rim

Frame and components attached to frame	
CR4	Mounting parts on frame/hole pattern
CL9	Steering LS 6/LS 8
KP6	AdBlue tank, 40 l
KS4	Main tank, 400 l, steel
K40	Tank-cap lock
K45	Screen, tank filler neck
KG0	Stainless-steel silencer with SCR cat. converter
K68	Exhaust silencer(s), vertical, behind cab
KE8	On-Board Diagnosis 1, with NOx check
C63	Bumper, steel version
C71	Rear underride guard (EC)

Brake system	
BB6	Drum brakes on front and rear axle
BB0	Anti-lock braking system (ABS), disengageable
BB8	Telligent braking system with ABS and ASR
B65	Compressed air dryer, heated
B43	Trailer brake, 2-line

Cab exterior	
F07	S cab
F24	Cab rear wall, straight
F35	Cab rear wall with window
FL6	Cab mountings, standard
Y69	Hydr. tilting mechanism oil, below -25 degrees C
FC7	Windows, tinted, without sun filter
D25	Roof hatch/vent, roof
FE6	Cab steps, movable
FS2	Wide-angle mirror on driver's side, heated
FX7	Front mirror, aerodynamic
FZ7	Immobiliser, with transponder

Cab interior	
SZ5	Dashboard and instrument cluster by Hirschman
EE6	Radio, truckline 65/70, CD player
EE8	Additional seats, 12V/15 A, firewall
FN1	Distribution cockpit
FE5	Power windows for driver's/co-driver's door
JK2	Instrument cluster, graphics-capable display

JD3	Tachograph, dig. EC, rpm+additional recorder, ADR
JZ2	Tachograph manufacturer Stoneridge
EG8	Radio, Truckline 65/70, CD player
HF1	Construction-site filter

Electrics / electronics	
EC6	Trailer socket, 15-pin
L04	Dim-dip lights, automatic
EK6	ADR provision, without chassis shielding
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control

Additional scopes	
X57	Noise reduction measures, EC 96/20
Y10	First aid kit
Y44	Hazard warning triangle
Y45	Warning lamp
Y33	Inflation assist, tapered wheels
Y34	Tire inflating hose, 10 m
Y28	2 wheel chocks
XK3	Powertrain warranty, Gen. Terms/Con., 3 yrs/250000 km
XS1	Labels/publications, Russian
ZZ3	Vehicle, for right-side traffic